

STRATHEARN

— STONE AND TIMBER.CO.UK —

Express Oak Specification Sheet

Product	Royale	
Engineered/Solid	Engineered	
Plank sizes	180x15mm	
Herringbone sizes	508x127x15mm	
Chevron sizes	N/A	
Other sizes	N/A	
Pack Size	180x15mm	2.376m ²
	508x127x15mm	0.387m ²
Grades available	Nature Grade Only	
Finishes available	Medium Brushed	
Oil finish	Hardened Oil	
Species	Sustainably Sourced European Oak	

	Plank	Herringbone
Suitable for use with UFH	✓	✓
Kiln dried to a moisture content 8-12%	✓	✓
Solid oak top layer thickness	3mm	3mm
End-matched timber (tongue & groove on 4 sides)	✓	✓
Lengths	Random up to 2.20m	508x127mm
Micro-bevelled board edges, as standard	✓	✓
Hand-scraped surface and edges optional for aged finish	x	x
Structural grade – install directly onto joists ≤ 400mm centres	x	x
Installation by secret nail onto suitable timber subfloor	x	x
Installation by gluing directly onto subfloor	✓	✓
Installation as a floating floor - room area ≤ 30m ² , room width ≤ 3m	✓	x
Construction	3 Layer	3 Layer
Suitable for installation in bathrooms/wcs	Contact Us	Contact Us

Bespoke materials available e.g. nosing, treads, edging pieces, radiator roses

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Plank Product Page [Click Here](#)

Herringbone Product Page [Click Here](#)

For care and maintenance information [Click Here](#)